


Specification	BLAZO X 48 10x4 CLS Tipper
GVW	47500 kg
Engine	mPower 7.2L Fuelsmart
Max. Power	206 kW @ 2200 r/min
Max. Torque	1050 Nm @ 1200 - 1700 r/min
Wheelbase	6770 mm
Gear Box	Eaton 9 Speed Manual Synchromesh
Clutch	395mm Diaphragm Type, Single Plate Dry Type
Gradeability	23%(Fly Up)
Suspension - Front	Parabolic Leaf Spring with Shock Absorber
Suspension - Rear	CLS
Rear Axle	Tandem Banjo Type Single Reduction
Tyres	11R20 - 16 PR
Fuel Tank Capacity	330L Heavy Duty Polyethylene (HDPE) Tank
Adblue Tank Capacity	50L
Chassis Cross Section(mm)	Ladder Type 285x70x8.5 (Reinforcement)
Steering	Hydraulic Power Assist Tilt & Telescopic
Brakes	Full Air S Cam Dual Circuit ABS 10 BAR System
System Voltage	24 V - 120AH
Cabin	Sleeper Cabin with AC
Max Speed	60 KMPH (Regulated)
Min Ground Clearance	250 MM
Body Size(cum)	29CBM - Box, 18CBM - Box
ATS System	BS6 Compliant - DOC + DPF
	SCR + ASC System + Mild EGR

Note: In view of our policy of continuously improving our products, we reserve the right to alter specifications or design without prior notice and without liability. Illustrations do not necessarily show the vehicle in its standard form. Accessories shown are not part of the standard equipment. Colour shades shown may vary. E. & O.E.











DUAL TYRE LIFT AXLE WITH SMART LIFT LOGIC

Smart Lift Logic is a feature incorporated in 12.5T lift axle which enables upward/downward movement of lift by synchronisation of signals. The movement of lift axle depends on:

- Load carried by the vehicle
- Turns negotiated by vehicle on Plain or Hilly terrains

Applications

















DEALER STAMP











