

Specifications

| MODEL | FURIO 10 | | |
|---------------------|--|----------|--|
| Engine | mDi Tech, 3.5L 4 Cylinder BSVI OBD2 with Fuel Smart Technology | | |
| Power | 91.5 kW @ 2500 rpm - Load Mode 79.5 kW @ 2500 rpm - Empty Mode | | |
| Torque | 375 Nm 1300 - 2000 rpm - Load Mode 325 Nm 1300 - 2000 rpm - Empty Mode | | |
| Clutch | Single Plate Dry Push Type with Clutch Booster Dia. 330 mm, B8090 LUK Liner | | |
| Transmission | MNT 55 with Neutral Start Switch 6F + 1R, Cable Shift | | |
| Rear Axle | Dana RA with RAR: 5.13 | | |
| Suspension | Front: Parabolic Leaf spring Rear: Semi elliptic leaf spring | | |
| Tyres | Front & Rear: 8.25 R 16 16PR | | |
| Cabin | 2.05m Furio Cabin | | |
| Brakes | 8.1 Bar Air Brakes w/o ABS | | |
| Ground Clearance | 220 mm | | |
| Gradeability | 29.40% | | |
| Battery | 12V, 100 Ah | | |
| Fuel Tank | 185L - Plastic tank | | |
| Ad Blue Tank | 13L | | |
| Cargo Body | 14Ft | 17.5Ft | |
| Cargo Body Variants | CBC, DSD | CBC, HSD | |
| GVW | 10350 kgs | | |
| FAW | 3250 kgs | | |
| RAW | 7100 kgs | | |
| Chassis | 210 x 65 x 5 mm | | |

Applications

























| Wheelbase | 3450 mm (14 Ft) | | 4000 mm (17.5 Ft) | |
|---------------------------|--------------------|--------------------|--------------------|--------------------|
| TCD | 12.9 m | | 14.9 m | |
| Variants | CBC | DSD | CBC | HSD |
| | - | | | Ç. |
| Cargo Body Dimension (mm) | NA | 4274 x 2135 x 600 | NA | 5334 x 2135 x 1745 |
| Overall Dimensions (mm) | 6067 x 2237 x 2455 | 6195 x 2350 x 2455 | 7135 x 2237 x 2455 | 7255 x 2280 x 2990 |

Note: In view of our policy of continuously improving our products, we reserve the right to alter specifications or design without prior notice and without liability. Illustrations do not necessarily show the vehicle in its standard form. Accessories shown are not part of the standard equipment. Colour shades shown may vary. E. & O.E.

















