

FURIO₁₆

**NOW EXPERIENCE COMFORT
AND SAFETY ON EVERY JOURNEY**



**MAHINDRA, INDIA'S
MOST FLUID-EFFICIENT
TRUCK RANGE.
GUARANTEED.**



**GET A 36-HOUR
GUARANTEED TURNROUND
AT WORKSHOP OR
GET ₹3,000 PER DAY.***



**GET BACK ON THE ROAD
IN 48 HOUR OR
GET ₹1,000 A DAY.***



**mahindra
iMAXX**

BS6 **obd2**

FURIO₁₆

Specifications

MODEL	FURIO₁₆		
Engine	mDi Tech, 3.5L 4 Cylinder BSVI OBD2 with Fuel Smart Technology		
Power	103kW @ 2400 rpm		
Torque	525 Nm 1250 - 1800 rpm - Heavy Mode 425 Nm 1250 - 1800 rpm - Light Mode		
Clutch	Single Plate Dry Push Type with Clutch Booster Dia. 362 mm, B8090 LUK Liner		
Transmission	MNT 55 with Neutral Start Switch 6F + 1R, Cable Shift		
Rear Axle	Meritor RA with RAR: 5.83		
Suspension	Front: Parabolic Leaf Spring Rear: Semi Elliptic Leaf Spring		
Tyres	Front & Rear: 9 R 20 16PR		
Cabin	2.05m Furio Cabin		
Brakes	10.1 Bar Air Brakes with ABS		
Ground Clearance	230 mm		
Gradeability	23%		
Battery	12V, 100 Ah		
Fuel Tank	190L - Metallic Fuel Tank		
Ad Blue Tank	35L		
Cargo Body	19Ft*	20Ft	22Ft
Cabin	Day, SL	Day, SL	Day, SL
Cargo Body Variants	POL CBC, 9KL WT	CBC, HSD, Container	CBC, HSD, Container
GVW	16140 kgs (15990 Kgs - 19Ft POL CBC*)		
FAW	5590 kgs		
RAW	10550 kgs		
Chassis	212 x 65 x 6 mm		

Applications




PARCELS & LOGISTICS



FRUITS & VEGETABLES



INDUSTRIAL GOODS



AUTO COMPONENTS



ELECTRONICS



MARKET LOADS



FMCG



CONTAINER



REEFER

Note: In view of our policy of continuously improving our products, we reserve the right to alter specifications or design without prior notice and without liability. Illustrations do not necessarily show the vehicle in its standard form. Accessories shown are not part of the standard equipment. Colour shades shown may vary. E. & O.E.

Wheelbase	4500 mm (19Ft Day)		4500 mm (19Ft SL)	4500 mm (20Ft Day)			4900 mm (20Ft SL)		4900 mm (22Ft Day)			5300 mm (22Ft)	
TCD	16.7 m		16.7 m	16.7 m			17.8 m		17.8 m			19.5 m	
Variants	POL CBC*	9KL WT	POL CBC*	CBC	HSD	Container	CBC	HSD	CBC	HSD-W	Container	CBC	HSD
LB Dimension (mm)	NA	4850 x 2100 x 1150	NA	NA	6098 x 2288 x 1980	6096 x 2286 x 2286	NA	6098 x 2374 x 1980	NA	6711 x 2374 x 1980	6703 x 2286 x 2286	NA	6711 x 2374 x 1980
Overall Dimensions (mm)	7790 x 2470 x 2590	7871 x 2470 x 2725	8110 x 2470 x 2590	8095 x 2470 x 2590	8095 x 2510 x 3356	8179 x 2426 x 3718	8415 x 2470 x 2590	8415 x 2560 x 3356	8700 x 2470 x 2590	8700 x 2560 x 3356	8785 x 2426 x 3719	9025 x 2470 x 2590	9025 x 2560 x 3356

