

LOADING optimo TIPPER

PERFECT FOR YOUR CONSTRUCTION NEEDS



GET A 36-HOUR
GUARANTEED TURNROUND
AT WORKSHOP OR
GET ₹3,000 PER DAY.*



GET BACK ON THE ROAD
IN 48 HOUR OR
GET ₹1,000 A DAY.*



To know more, give us a missed call on:
1800 315 7799

mahindra
iMAXX

BS6 **obd2**



LOADING
optimo TIPPER

Specifications

MODEL	
Engine	mDi, CRDe, 2.5L 4 Cylinder BSVI OBD2
Power	60.5kW @ 3200 rpm
Torque	220 Nm 1400 - 2000 rpm
Clutch	Single Plate Dry Dia. 280 mm
Transmission	MNT 40 C (5 + 1) Cable Shift FGR: 6.795
Suspension	Front & Rear : Semi Elliptic Leaf Spring with ARB at Front
Tyres	Front: 7.5 X 16 16PR Rib Rear: 7.5 X 16 16PR Lug
Cabin	1.7m Cabin
Brakes	Hydraulic Vacuum Assisted
Ground Clearance	190
Gradeability	30.5%
Battery	12V, 100 Ah
Fuel Tank	60L - Metallic Tank
Ad Blue Tank	13L
Cargo Body Variants	CBC, Fully Built Tipper
GVW	6950 kgs
FAW	2130 kgs
RAW	4820 kgs
Chassis	171 x 65 x 5 mm

Applications



Wheelbase	2500 mm	
TCD	11.9 m	
Variants	CBC	Fully Built Tipper
		
Cu. Capacity	NA	2.8 Cu. M
Cargo Body Dimension (mm)	NA	3125 x 1692 x 530
Overall Dimensions (mm)	4685 x 1920 x 2210	4980 x 1950 x 2285

Note: In view of our policy of continuously improving our products, we reserve the right to alter specifications or design without prior notice and without liability. Illustrations do not necessarily show the vehicle in its standard form. Accessories shown are not part of the standard equipment. Colour shades shown may vary. E. & O.E.